



Ampliroll®

13,000 POUNDS

90 SERIES



Why buy a HookLift?

Do you have trucks that are not always being used?
Do you have a difficult time finding quality drivers?
Is there a piece of equipment you could use, but
can't justify adding another truck?

**It's Multi-tasking for your truck.
The possibilities are Infinite.**

With an Ampliroll® you can do just about anything.

Deliver — Load — Dump



FEATURES

- **Sliding Jib** gives you greater range of body lengths and optimal weight distribution.
- **Twin Pivot** allows you to dump a uniform pile of material.
- **Dual Cylinders** gives greater stability while dumping and loading.
- **Safely** operated from the drivers seat.
- **Dock Level** loading and unloading.
- **Double** your payload by pulling another body on a trailer.
- **Maneuverable** to operate, the container can be loaded within a **60 degree** arc.
- **Spot** the container exactly where you want it, by pushing it into place with no damage.
- **Quickly** loads a body in less than one minute.
- **Investment** that will outlast your truck, Amplirolls® will last over **25 years**.
- Meets all highway safety standards.



The Ampliroll® HookLift was invented in 1969. Our process of laser cutting and robotic welding enables us to provide you with a complete line of hooklifts, that eliminate the use of **SHIMS** and **WEAR PADS**.

***Ampliroll® has been imitated
but never duplicated.
Compare the difference before you buy.***



Ampliroll® Model	AL 90S-12	AL 90L-14
Lifting Capacity (including container)	13,000 lbs	13,000 lbs
Shipping Weight	1790 lbs.	1790 lbs.
Dump Angle	58 degrees	61 degrees
Cab to Axle	84 to 108 inches	108 to 126 inches
Over-All Length	126 inches	144 inches
Body Length	9 to 13.5 feet	10 to 14 feet
Hydraulic Specifications:		
Pump - Axial piston, 5,700 psi, 7 GPM @ 1,200 RPM, SAE B, direct mount		
Controls - Electric in cab		
Reservoir - 7 gallons		
Filter - 10 micron, return line with replaceable cartridge		
Maximum operating pressure - 5,000 psi		
Hoses, tubes & fittings all JIC/SAE specifications		
Steel: Special Alloy	ASTM A 514 in jib, central arm and tilting frame ASTM A 572 grade 60 type 2 subframe	
Safety Devices:	Counter-balance valve to hold cylinder if hose breaks. Hoist automatically locks into dump mode when container is locked into holdowns.	
Truck Requirements:	GVWR - 15,000 to 20,000 lbs	

Notice: Longer containers may not comply with I.C.C. bumper regulations and can effect dump angle.

Inside Controls



Distributed by:



marrel
CORPORATION

4750 14 Mile Road NE

Rockford, MI 49341

Phone: (616) 863-9155

Fax: (616) 863-9177

Toll Free: (866) 822-3580

E-mail: equipment@amplirollusa.com

www.amplirollusa.com