



1



. . .



Rugby<sup>®</sup> customers have come to expect the high quality and durability in which our bodies are built, and Rugby looks forward to the challenges of producing bodies that meet the needs and high demands of our customers.

As a result, we now present our TITAN SERIES Dump Body Line. Featuring a dirt-shedding top rail, 10 degree sloped tailgate, and radius front corner posts, the TITAN SERIES Bodies have a sleek yet strong new look.

When choosing a Dump Body - look to Rugby for top quality and economical pricing.

## TAILGATE FEATURES & SPECIFICATIONS:

- Sloped 10 degree inward and recessed flush with rear face of corner posts.
- Four-way tailgate with adjustable rod on trip lever.
- Fully boxed frame, reinforced with two tapered vertical braces and one tapered horizontal brace.
- Angle iron reinforced decking at rear, ensures longer lasting gate seal.
- Heavy duty 1.25" lower pins on tailgate, upper pivot arms are of .75" plate.
- Grease fittings on upper pivot arms.
- Equipped with spreader chains and banjo eye chain holders in corner posts.
- Optional coal chute door. -
- Optional spreader apron.
- Optional air tailgate.

NOTE: See chart for side height and tailgate height on all Titan Series Dump Bodies.

RUGBY DUMP BODY SPECIFICATION						
Body Length	10'	10'	10'	12'		
Body Capacity (cubic yds)	4-5	5-7	6-8	6-8		
Side Height (in)	20	24	30	24		
Tailgate Height (in)	26	34	40	34		
Body Weight (lbs)	1875	2160	2260	2500		

Accept only original Rugby Truck Hoists

#### **Commitment to Quality**

Today's marketplace demands quality products and competitive pricing. We work hard at Rugby to comply with your needs. Our reputation since 1969 has been one of quality production and we won't change. You deserve and demand what we are committed to, the best.



### RUGBY MANUFACTURING

Rugby, ND • 701-776-5722 • FAX 701-776-6235 www.rugbymfg.com • E-mail sales@rugbymfg.com

#### Sold by:



# **REALITY TITAN SERIES**

#### FEATURES & SPECIFICATIONS FOR 5-7 & 6-8 YARD BODIES:

- 10 gauge steel (50 grade) on side construction.
- 8 gauge steel floor with radius corners.
- 10 foot 6-8 yard body standard all 8 gauge.
- Sides equipped with brackets for sideboard extensions.
- Fully boxed dirt-shedding top rail.
- 45 degree sloped rub rail.
- Three vertical boxed braces per side.
- Radius front corner posts with recessed clearance lights on lower post.
- Tapered Full height rear corner posts 5 inches deep.
- Front has fully boxed top rail with v-bend reinforced front panel.
- 7" structural channel long sills and 4" I beam cross sills on 12" centers.
- Recessed shock resistant rubber mounted, clearance lights, also three cluster lights provided in lower apron.
- New oval-shaped stop/turn/tail lights in upper rear corner posts
  with side clearance lights on lower post.
- 2 part epoxy primer.
- All appearance corners have radius bends.
- Sloped ½ cab shield.
- Optional <sup>3</sup>/<sub>4</sub> cab shield.
- Optional all 8 gauge on 5⁄7 yard dump body.
- Optional LED Lights available.



Rugby products feature light locations that may assist the installer in meeting FMVSS / CMVSS 108.

HOIST SPECIFICATIONS	SF-26	SF-623	SF-28	SF-2355
NTEA Class	50	50	60	60
Cyl. Bore & Stroke	6" x 20"	6" x 23"	6" x 28"	⅔" x 23"
Chrome Cyl. Shaft	21⁄2"	2½"	2½"	2"
Operating Pressure (psi)	3200	3200	3200	3200
Hoist Weight (lbs)	970	1060	1040	1170
Hoist Tonnage 10' Body	12.5T	17T		22T
Hoist Tonnage 12' Body			15T	18T

Caution: The Combined Weights of Truck Chassis, Hoist, Body & Cargo Must Not Exceed The Gross Vehicle Weight Rating (GVWR) Of The Truck!



